


Exterior Nails

Finishing Nail


Features:

- Brad head for a less-visible appearance
- Smooth shank, diamond point for easier driving
- Choose Type 316 stainless steel for seaside applications and superior corrosion resistance



Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
2d	1	15	0.072	$\frac{6}{55}$	0.109	863	T2FN1	—	T2FNB
3d	1¼	15	0.072	$\frac{6}{55}$	0.109	649	T3FN1	T3FN5	T3FNB
4d	1½	14	0.083	$\frac{3}{25}$	0.120	434	T4FN1	T4FN5	T4FNB
5d	1¾	14	0.083	$\frac{3}{25}$	0.120	375	T5FN1	—	—
6d	2	13	0.092	$\frac{5}{37}$	0.135	247	T6FN1	T6FN5	T6FNB
8d	2½	12	0.113	$\frac{4}{27}$	0.148	146	T8FN1	T8FN5	T8FNB
10d	3	11	0.120	$\frac{16}{97}$	0.165	102	T10FN1	—	T10FNB
12d	3¼	11	0.120	$\frac{16}{97}$	0.165	97	T12FN1	T12FN5	—
16d	3½	11	0.120	$\frac{16}{97}$	0.165	86	T16FN1	T16FN5	T16FNB



Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
2d	1	15	0.072	$\frac{6}{55}$	0.109	863	S2FN1	—	S2FNB
3d	1¼	15	0.072	$\frac{6}{55}$	0.109	649	S3FN1	S3FN5	S3FNB
4d	1½	14	0.083	$\frac{3}{25}$	0.120	434	S4FN1	S4FN5	S4FNB
5d	1¾	14	0.083	$\frac{3}{25}$	0.120	375	S5FN1	—	S5FNB
6d	2	13	0.092	$\frac{5}{37}$	0.135	247	S6FN1	S6FN5	S6FNB
8d	2½	12	0.113	$\frac{4}{27}$	0.148	146	S8FN1	S8FN5	S8FNB
10d	3	11	0.120	$\frac{16}{97}$	0.165	102	S10FN1	S10FN5	S10FNB
12d	3¼	11	0.120	$\frac{16}{97}$	0.165	97	—	—	S12FNB
16d	3½	11	0.120	$\frac{16}{97}$	0.165	86	S16FN1	S16FN5	S16FNB