



A510300

Reusable Swivel Concrete Anchor

FEATURES

- Push button removal, no tools required
- Rigid and durable tri-wedge design
- 2 inch, swivelling connecting D-ring
- Minimum Breaking Strength (MBS): 5,000 pounds
- 360 degree loading
- Horizontal, vertical, or overhead use
- Stainless steel construction
- Meets ANSI Z359.18-2017, Type A

R3™ CONCRETE ANCHOR

RAPID • RIGID • REUSABLE



SPECIFICATIONS

Model No.	Material	Length	Width	Connection Size	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A510300	Stainless Steel Glass Filled Nylon	7.5 in (19.1 cm)	2.7 in (6.8 cm)	2 in (5.1 cm)	5,000 lbs (22.2 kN)	0.7 lbs (0.35 kg)	ANSI Z359.18-2017 Type A OSHA 1910 & 1926

*See User Instructions for more information.

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet